

Frequency hopping method for RFID Tag

FIELD OF THE INVENTION

The field of the invention is the field of radio frequency (RF) identification (RFID) transponders (tags), and systems for their use.

BACKGROUND OF THE INVENTION

RF Transponders (RF Tags) can be used in a multiplicity of ways for locating and identifying accompanying objects and transmitting information about the state of the object. It has been known since the early 60's in U.S. Pat. No. 3,098,971 by R.M. Richardson, that electronic components of transponders could be powered by radio frequency (RF) electromagnetic (EM) waves sent by a "base station" and received by a tag antenna on the transponder. The RF EM field induces an alternating current in the transponder antenna which can be rectified by an RF diode on the transponder, and the rectified current can be used for a power supply for the electronic components of the transponder. The transponder antenna loading is changed by something that was to be measured, for example a microphone resistance in the cited patent. The oscillating current induced in the transponder antenna from the incoming RF energy would thus be changed, and the change in the oscillating current led to a change in the RF power radiated from the transponder antenna. This change in the radiated power from the transponder antenna could be picked up by the base station antenna and thus the microphone would in effect broadcast power without itself having a self contained power supply. The "rebroadcast" of the incoming RF energy is conventionally called "back scattering", even though the transponder broadcasts the energy in a pattern determined solely by the transponder antenna. Since this type of transponder carries no source of energy of its own, it is called a "passive" transponder to distinguish it from a transponder containing a battery or other energy supply, conventionally called an active transponder. The power supply of the passive transponder is typically a capacitor which is charged by rectifying the RF power signal sent out by the base station, but may be any source of power which is energized by an external signal.

1 Active transponders with batteries or other independent energy storage and supply means
2 such as fuel cells, solar cells, radioactive energy sources etc. can carry enough energy to
3 energize logic, memory, and tag antenna control circuits. However, the usual problems with life
4 and expense limit the usefulness of such transponders.

5 In the 70's, suggestions to use backscatter transponders with memories were made. In this
6 way, the transponder could not only be used to measure some characteristic, for example the
7 temperature of an animal in U.S. Pat. No. 4,075,632 to Baldwin et. al., but could also identify the
8 animal.

9 The continuing march of semiconductor technology to smaller, faster, and less power
10 hungry has allowed enormous increases of function and enormous drop of cost of such
11 transponders. Presently available research and development technology will also allow new
12 function and different products in communications technology. However, the new functions
13 allowed and desired consume more and more power, even though the individual components
14 consume less power.

15 It is thus of increasing importance to be able to power the transponders adequately and
16 increase the range which at which they can be used. One method of powering the transponders
17 suggested is to send information back and forth to the transponder using normal RF techniques
18 and to transport power by some means other than the RF power at the communications
19 frequency. However, such means require use of possibly two tag antennas or more complicated
20 electronics.

21 Sending a swept frequency to a transponder was suggested in U.S. Pat. No. 3,774,205.
22 The transponder would have elements resonant at different frequencies connected to the tag
23 antenna, so that when the frequency swept over one of the resonances, the tag antenna response
24 would change, and the backscattered signal could be picked up and the resonance pattern
25 detected.

26 Prior art systems can interrogate the tags if more than one tag is in the field. U.S. Pat. No.
27 5,214,410, hereby incorporated by reference, teaches a method for a base station to communicate
28 with a plurality of tags .

29 Sending at least two frequencies from at least two antennas to avoid the "dead spots"
30 caused by reflection of the RF was proposed in EPO 598 624 A1, by Marsh et al. The two

1 frequencies would be transmitted simultaneously, so that a transponder in the "dead spot" of one
2 frequency would never be without power and lose its memory of the preceding transaction.

3 The prior art teaches a method to interrogate a plurality of tags in the field of the base
4 station. The tags are energized, and send a response signal at random times. If the base station
5 can read a tag unimpeded by signals from other tags, the base station interrupts the interrogation
6 signal, and the tag which is sending and has been identified, shuts down. The process continues
7 until all tags in the field have been identified. If the number of possible tags in the field is large,
8 this process can take a very long time. The average time between the random responses of the
9 tags must be set very long so that there is a reasonable probability that a tag can communicate in
10 a time window free of interference from the other tags.

11 In order that the prior art methods of communicating with a multiplicity of tags can be
12 carried out, it is important that the tags continue to receive power for the tag electronics during
13 the entire communication period. If the power reception is interrupted for a length of time which
14 exceeds the energy storage time of the tag power supply, the tag "loses" the memory that it was
15 turned off from communication, and will restart trying to communicate with the base station, and
16 interfere with the orderly communication between the base station and the multiplicity of tags.

17 The amount of power that can be broadcast in each RF band is severely limited by law
18 and regulation to avoid interference between two users of the electromagnetic spectrum. For
19 some particular RF bands, there are two limits on the power radiated. One limit is a limit on the
20 continuously radiated power in a particular bandwidth, and another limit is a limit on peak
21 power. The amount of power that can be pulsed in a particular frequency band for a short time is
22 much higher than that which can be broadcast continuously.

23 Federal Communications Commission Regulation 15.247 and 15.249 of Apr. 25, 1989
24 (47 C.F.R. 15.247 and 15.249) regulates the communications transmissions on bands 902-928
25 MHZ, 2400-2483.5 MHZ, and 5725-5850 MHZ. In this section, intentional communications
26 transmitters are allowed to communicate to a receiver by frequently changing frequencies on
27 both the transmitter and the receiver in synchronism or by "spreading out" the power over a
28 broader bandwidth. The receiver is, however, required to change the reception frequency in
29 synchronism with the transmitter.

RELATED PATENTS AND APPLICATIONS

The following U. S. Patents and Patent Applications are assigned to the assignee of the present invention: U.S. Patents : 6,320,896, 6,327,312, 6,005,530, 6,122,329, 6,501,807, 6,294,997, 6,166,638, 6,441,740, 6,104,291, 5,939,984, 6,140,146, 6,259,408, 6,236,223, 6,249,227, 6,201,474, 6,100,804, 6,294,996, 6,486,769, 6,121,880, 6,518,885, 6,593,845, 6,320,509, 6,639,509, 5,485,520, 6,275,157, 6,285,342, 6,366,260, 6,215,402, 6,118,379, 6,177,872, 6,281,794, 6,130,612, 6,147,606, 6,288,629, 6,172,596, 6,566,850, 6,535,175; 5,850,181; 5,828,693; ; and U.S. Patent Applications 09/394,241 filed 09/13/1999, 10/056,398 filed 01/23/2002, and 60/459,414 filed 03/31/2003. The above patents and patent applications are hereby incorporated by reference.

OBJECTS OF THE INVENTION

It is an object of the invention to produce a method, an apparatus, and a system communicating between a base station and at least one tag which decreases the time taken to identify the tag or tags.

SUMMARY OF THE INVENTION

Information is communicated between a base station and at least one tag by sending RF power P_j for a first time t_j to the tag at a first frequency f_j from the base station to the tag, then sending power for a second time t_k to the tag at a second frequency f_k , where t_j and t_k are substantially different times.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is the power and FIG. 1B is the frequency transmitted as a function of time in the prior art.

FIG. 2A is the power and FIG. 2B is the frequency transmitted as a function of time in one of the preferred methods of the invention.

FIG. 3 is block diagram of a preferred method of the invention.

DETAILED DESCRIPTION OF THE INVENTION

United States Patent 5,828,693 to Mays, et al. issued October 27, 1998 entitled Spread spectrum frequency hopping reader system and United States Patent 5,850,181 to Heinrich, et al. issued December 15, 1998 entitled Method of transporting radio frequency power to energize radio frequency identification transponders, assigned to the assignee of the present invention, give details on RFID tags powered by an RF field where the frequency sent to the tags hops from frequency to frequency chosen from a pseudorandomly ordered list of frequencies. In both the above described patents, the RF field is sent out to the tags from a base station as a series of bursts of power at a particular frequency, with the frequency changing for the next burst, but the power and the length of time of the bursts are kept constant. Patent 5,828,693 teaches that the length of time of each burst the regular series of bursts may be changed to avoid having one or more base stations interfering with one another. Apparatus and methods for changing the frequency and the power sent out by the tags are well described in these patents. The above patents are hereby incorporated by reference.

In a preferred communication between a base station and a group of tags, each tag is identified, and then instructed to take no further part in the communication unless it is called upon to do so by calling its identification number. Since two tags "talking" at the same time to the base station will interfere with each other, a tag which has once been identified, and which loses its "memory" that it was identified, will slow the communication with the group down because it will have to be re-identified and re-instructed to keep silence. In the patent 5,850,181 referred to above, the importance of keeping the tag functional by not allowing the

1 power in the tag to drop below a minimum was pointed out. In a preferred embodiment, well
2 described in copending application 10/056398 assigned to the assignee of the present invention
3 filed January 23, 2002 by Heinrich et al., power is provided for a long time t_0 to just one
4 device or function on the tag... the device or "flag" which tells the tag that it has been identified.
5 A separate power supply such as a capacitor is provided which provides power only to the flag
6 for a time t_0 long compared to the normal tag power down time when all the tag electronics are
7 drawing current (which could be as short as 50 microsec). Such a situation may occur, for
8 example, when the frequency sent to the tag changes, and the tag is in a position where multipath
9 effects drop the power received by the already identified tag below that power which the tag
10 needs to be fully functional. If the tag flag remains set until the frequency is changed again and
11 the multipath transmission changes so the tag is powered once again, the tag remembers that it
12 has been identified, and does not interrupt communications by trying to contact the base station.
13 The above application 10/056398 is hereby incorporated by reference.

14 When a group of tags is being interrogated by a base station, the base station according to
15 the prior art sends out signals at a frequency f_i for a fixed time t_i , and then changes frequency to
16 another frequency f_j chosen from a list of frequencies listed in pseudorandom order, and then
17 sends frequency f_j for the same time t_i . This process is continued until all tags have been
18 identified. It may be, however, that the base station sends out a command for unidentified tags
19 in the field to respond, and no tags respond, either because all tags in the field have been
20 identified or because some tags in the field do not receive power because of the above identified
21 multipath problems. Presently, the base station continues to send power at the same frequency
22 and power for the same amount of time regardless of whether a tag in the field responds. The
23 base station continues through the pseudorandomly ordered list of frequencies, and either stops
24 transmission or starts again at the beginning of the list. Patent number 5,828,693 mentions that
25 the amount of time that a base station sends out a particular frequency before the frequency
26 changes may be changed, but does not state conditions for such changes. In particular, Patent
27 number 5,828,693 does not specify that the length of time taken to change the time interval shall
28 be less than the time taken to power down the tag or the time for the flag to reset.

29 In the most preferred method of the present invention, the base station changes frequency
30 as soon as no tags respond, so that those unidentified tags which are silent because they are in a

1 multipath power minimum at frequency f_j will see a different frequency f_{j+1} , for which the
 2 multipath minima are in a different spatial positions. For example, at 2.4 GHz, the frequency
 3 might be changed in the prior art every 300 or 400 msec. However, the base station can tell if
 4 one or more tags is responding in as little as 10 ms. Thus, the base station will change
 5 frequencies in as little as 10 or 20 ms as soon as no more tags respond. Preferably, when the
 6 time is changed from a time t_j to another time t_{j+1} , t_{j+1} will be less than $t_j / 2$. More
 7 preferably, t_{j+1} will be less than $t_j / 4$, and most preferably t_{j+1} will be less than $t_j / 10$. To take
 8 into account that t_{j+1} may also be longer than t_j , preferably $|t_{j+1} - t_j| > 0.05 (t_j + t_{j+1})$, more
 9 preferably $|t_{j+1} - t_j| > 0.1 (t_j + t_{j+1})$ and most preferably $|t_{j+1} - t_j| > 0.3 (t_j + t_{j+1})$.

10 Fig. 1A and 1B show the prior art sent out RF power and frequency as a function of time.
 11 The frequency is changed at regular times, and the power is greatly reduced as the frequency is
 12 changed. Fig. 2A shows a sketch of RF power as a function of time for the method of the
 13 invention. After sending out a power P_i at a frequency f_i for a time t_i , the frequency is
 14 changed and a new frequency chosen in order from a list of frequencies listed in pseudorandom
 15 order. Instead of sending a new frequency f_j for the same time t_i , the frequency f_j is sent out
 16 for a time t_j which is substantially different from t_i . The time taken to change the frequency
 17 from f_i to f_j and the timing from t_i to t_j must be less than the time t_0 for the tag flag to be
 18 reset, and is preferably less than the time taken for the tag to power down once the RF field
 19 drops to zero. While the power levels sent out in fig. 2A are shown to be constant with time, the
 20 invention anticipates that the power level sent out may change as a function of time. The power
 21 level may be an increasing or decreasing staircase function, or indeed any regular function of
 22 time.

23 Fig. 3 shows a block diagram of the most preferred method of the invention. The base
 24 station starts by choosing the first frequency in the ordered list and sets $j = 1$ in step 300.
 25 Then, the base station sends out RF energy at a frequency f_j for a time sufficient for a single tag
 26 to respond in step 310. In decision step 320, the base station decides whether one or more tags
 27 responded. If one or more tags responded, another decision step 320 decides whether the total
 28 time t_j spent sending out frequency f_j exceeds a maximum time limit t_{max} for sending out a
 29 single frequency at the power sent. Government regulations prohibit power of over a certain
 30 limit being sent out for more than a defined time. The protocol sets a maximum time limit t_{max}

1 (which may optionally depend on power sent out) for sending out one frequency, and when that
2 time limit has been exceeded, the index j is changed to $j + 1$ in step 340, and the system
3 returns to step 310 to send out another the next frequency f_{j+1} in the lists. If no tags responded
4 in step 320, the system goes immediately to step 340 and to change frequency to the next
5 frequency f_{j+1} in the list.

6 In the most preferred method of the invention, the maximum time t_{max} for sending out a
7 single frequency may be reached while the first frequency is being sent out, since there are many
8 unread tags in the field. Eventually, however, most tags have been read, and at that time, no
9 tags return signals before the maximum time t_{max} has been reached. Then, the base station
10 cycles through the remaining frequencies in the list, or the base station decides that all tags have
11 been identified, and starts the remainder of the protocol for communicating with the tags. It is
12 anticipated by the inventors that the time for sending out the frequency f_{j+1} in the list of
13 frequencies could in fact be longer than the time for sending out the prior frequency f_j , as new
14 tags could move into the field during the communication procedure.

15 It is anticipated by the inventors that the base station could send out various power levels
16 during the communication, since fewer tags would be in effective communication with the base
17 station if the sent out power was lower, and hence the fewer tags could be identified rapidly.
18 Then, the power could be raised to "catch" more of the tags in the field. Alternatively, the
19 power could be sent out high at first, and if more than one tag responds the power could be
20 reduced to reduce the number of tags in effective communication with the base station.

21 Obviously, many modifications and variations of the present invention are possible in
22 light of the above teachings. It is therefore to be understood that, within the scope of the
23 appended claims, the invention may be practiced otherwise than as specifically described.